



ROOFING UNDERLAYMENT



100% Recycle



Water Repellent



Non-Absorbent



Epilay® GripWalk® is our unique high-traction top layer which reduces heat and provides a cooler working surface. GripWalk®'s textured walking surface permits easier walkability on steep slopes and retains its non-slippery properties even during high condensation and moisture on the surface.



Epilay® SkidResist® is a very high anti-skid bottom layer made with superior technology and advanced polymers that helps keep the underlayment intact and prevents the fabric from tearing while it is being fastened, avoiding any leakages. Ensuring enhanced stability and safety.

Epilay™ ProtectTite™ specific product features:

Mechanically Fastened Underlayments

ProtectTite™ SUPERIOR

- Specifically manufactured to replace the 15# and 30# felt
- **7 mil thickness** - a 10 square roll weights only 23 lbs!
- **Works best for use under Asphalt shingles & Metal Roofs**
- 5 times lighter and 25 times stronger than 15# felt
- **15 year limited warrant**

ProtectTite™ ULTRA

- Specifically manufactured to replace the 30# felt
- **11 mil thickness** - a 10 square roll weights only 29 lbs!
- **Works best for use under Metal, Shake and Asphalt shingles**
- 10 times lighter and 25 times stronger than 30# felt
- **30 year limited warranty**

ProtectTite™ PLATINUM

- Specifically manufactured to replace the 30# felt
- **17 mil thickness** - a 10 square roll weights only 37 lbs!
- Works best for use under Metal, Shake, Asphalt, Concrete, and Slate shingles
- 8 times lighter and 35 times stronger than 30# felt
- **40 year limited warranty**

ProtectTite™ PLASTFELT™

- Specifically manufactured to replace the #15 felt and #30 felt
- **6.5 mil thickness**
- Works best for use under Asphalt Shingles & metal roofs.
- 25 times stronger than 15# felt and 5x lighter than 15# felt
- **10 year limited warranty**

Self Adhered (Peel & Stick) Underlayments

PlyStik™ Plus

- Specifically manufactured to replace the traditional asphalt based Sand and Granular Peel & Stick Underlayments.
- High temp
- **48 mil thickness**
- Works best for use under Metal, Shake, concrete tiles, slates & asphalt shingles
- 5 times lighter and 25 times stronger than #15 felt.
- **Limited lifetime warranty**

PlyStik SA-250

- Specifically manufactured to replace the traditional asphalt based Sanded and Granular Peel & Stick Underlayments.
- High temp
- **Nominal 60 mil thickness**
- Works best for use under Metal, Shake, concrete tiles, slates & asphalt shingles
- **Limited Life time limited warranty**

